

Mixed Flow Hooded Rooftop Supply or Exhaust Fans

Model XRID

When ventilating commercial kitchens, finding a product that combines reliable performance with configurable design options is essential, but not always easy. Fortunately, Accurex direct drive hooded rooftop fans are now available for both roof supply and exhaust, using our latest mixed flow wheel technology to enable a small footprint and quiet operation. They are powered by totally enclosed motors that are quickly accessible for serviceability, and available with the efficient Greenheck Vari-Green® motor that saves energy and costs. Take your airflow performance through the roof with Accurex model XRID fans

Flexible Design, Dependable Results

SIZES AND CONFIGURATIONS

- Direct drive, 12 fan sizes, 7-33
- Supply available with birdscreen as standard or optional 1-inch washable aluminum filters
- Exhaust available with birdscreen as standard

Exhaust Fan with Birdscreen

PERFORMANCE

- Supply: Up to 27,100 cfm
- Exhaust: Up to 25,200 cfm
- Up to 3 in. of static pressure

PRIMARY APPLICATIONS

- Filtered and Unfiltered Roof Supply
- Roof Exhaust
- Clean Air Environments
- High Efficiency
- Low Sound



THE ACCUREX ADVANTAGE



MIXED FLOW WHEEL
IMPROVES AIRFLOW AND
EFFICIENCY WHILE REDUCING
SOUND AND FOOTPRINT



DIRECT DRIVE MOTOR IS TOTALLY ENCLOSED FOR IMPROVED SERVICEABILITY AND HAS NO BELT OR MOTOR COVER TO MAINTAIN



GREENHECK VARI-GREEN®
HIGH-EFFICIENCY MOTOR
REQUIRES LESS MAINTENANCE
AND REDUCES OPERATING
COSTS BY AROUND 30-50%
COMPARED TO OTHER MOTORS



PANEL OPENINGS ON BOTH SIDES OF THE UNIT PROVIDE QUICK ACCESS FOR SIMPLIFIED INSPECTION



LIFTING LUGS ALLOW FOR EASY RIGGING AND INSTALLATION



HIGH-QUALITY CONSTRUCTION INCLUDES GALVANIZED STEEL HOODS BUILT FOR STRENGTH AND DURABILITY

OPTIONAL FEATURES & ACCESSORIES

- Greenheck Vari-Green® motor available for motor sizes through 10 hp
- · Aluminum hood
- Spark B & C resistant construction
- Duct adapters
- 1-inch aluminum filters (supply only)
- Decorative and protective coatings
- · Disconnect switches
- · Backdraft and control dampers
- · Multiple control options
- · Roof curbs and accessories





Vari-Green® Motors and Controls



Aluminum Filters







Model XRID is compliant with Miami-Dade NOA requirements and carries Florida Product Approval. Sizes 7 through 24 are rated to ±90 psf, while sizes 27 through 33 are rated to ±40 psf.



Our Commitment: As a result of our commitment to continuous improvement, Accurex reserves the right to change specifications without notice. Specific Accurex product warranties are located on accurex.com within the product area tabs and in the Library under Warranties.